

## [2017 New Free Share 200-310 PDF Dumps With Lead2pass Updated Exam Questions (181-200)]

2017 July Cisco Official New Released 200-310 Dumps in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed! As a professional IT exam study material provider, Lead2pass gives you more than just 200-310 exam questions and answers. We provide our customers with the most accurate study material about the 200-310 exam and the guarantee of pass. We assist you to prepare for 200-310 certification which is regarded valuable the IT sector. Following questions and answers are all new published by Cisco Official Exam Center: <https://www.lead2pass.com/200-310.html>

QUESTION 181A data center is being deployed, and one design requirement is to be able to readily scale server virtualization. Which IETF standard technology can provide this requirement? A. Transparent Interconnection of Lots of LinksB. Cisco FabricPathC. data center bridgingD. Cisco Unified FabricAnswer: A

QUESTION 182A company would like to distribute a VM hosting cluster between three data centers with the capability to move VMs between sites. The connectivity between data centers is IP only, and the new design should use the existing WAN. Which Layer 2 tunneling technology should be used? A. VPLSB. L2TPv3C. OTVD. AToM Answer: C

QUESTION 183In which two places is redundancy recommended in an enterprise campus network design? (Choose two.) A. building distributionB. campus coreC. building accessD. e-commerceE. Internet connectivity Answer: AB

QUESTION 184What are two purposes of route redundancy? (Choose two.) A. minimize the effect of link failuresB. minimize the effect of internetworking device failuresC. minimize the convergence time of STPD. load balance across redundant pathsE. save network costs Answer: AB

QUESTION 185Which two statements are true regarding a hierarchical network? (Choose two.) A. facilitates choosing the type of routing protocols to be used in the network B. provides scalability without affecting other layers and functionalityC. provides better performance as network resources are efficiently utilizedD. limits redundancy at the distribution layerE. complicates manageability because of the added security Answer: BC

QUESTION 186Which two Cisco data center devices can participate in Cisco FabricPath? (Choose two.) A. Cisco Nexus 5500 Series SwitchesB. Cisco Nexus 1000V Series SwitchesC. Cisco Nexus 7000 Series SwitchesD. Cisco Nexus 4900 Series SwitchesE. Cisco MDS 9500 Series Multilayer Directors Answer: AC

QUESTION 187Refer to the exhibit. Assuming that a network will grow exponentially for the next 24 months, what is the main limitation that must be addressed? A. scalabilityB. serviceabilityC. redundancyD. resiliency Answer: A

QUESTION 188A network engineer is tasked with summarizing the routes to a remote site. What is the optimal route statement to connect to the 192.168.101.0/24 and 192.168.102.0/24 networks across the corporate WAN? A. ip route 192.168.100.0 255.255.254.0 10.1.1.1B. ip route 192.168.100.0 255.255.252.0 10.1.1.1C. ip route 192.168.100.0 255.255.255.0 10.1.1.1D. ip route 192.168.101.0 255.255.254.0 10.1.1.1 Answer: B

QUESTION 189Refer to the exhibit. Where should routes in the routing table be aggregated or summarized? A. in the core toward the data centerB. in the distribution toward the accessC. in the core toward the distributionD. in the distribution toward the core Answer: D

QUESTION 190Which option is used by OSPF to reduce the flooding domain of database updates in a network? A. hello packetsB. virtual linksC. interface costD. areas Answer: D

QUESTION 191Refer to the exhibit. Which three OSPF routers are the only routers that may perform summarization with the current network layout? (Choose three.) A. Router 2B. Router 3C. Router 4D. Router 5E. Router 7F. Router 8 Answer: ACE

QUESTION 192Which two options should be used to achieve fast convergence in an OSPF network? (Choose two.) A. Bidirectional Forwarding DetectionB. fast hellosC. LSA retransmission intervalD. SPF throttle timersE. LSA group pacing Answer: AB

QUESTION 193Refer to the exhibit. Which next hop will the router select if given an IP packet with the destination address 19.48.254.3? A. Router 2B. Router 1C. Interface 0D. Interface 1 Answer: A

QUESTION 194Refer to the exhibit. In this suboptimal design of a homogeneous Cisco network, which version of spanning tree provides the fastest convergence? A. PVST+B. CSTC. RPVSTD. VSTPE. PVST Answer: C

QUESTION 195Refer to the exhibit. The red lines refer to STP blocked ports. What happens if the HSRP active moves to the right distribution, and the STP root remains on the left distribution? A. The STP root becomes the gateway.B. The interdistribution link is used for transit.C. The HSRP standby becomes the gateway.D. The interaccess link is used for transit.E. Host traffic is unable to reach the HSRP active. Answer: B

QUESTION 196Refer to the exhibit. The organization is migrating away from FHRP. VSS has been implemented on a pair of Cisco Catalyst 6500 Series Switches. In order to avoid changes to end hosts, the default gateway is carried over to the SVI on the VSS. Why does the implementation plan require a four-hour wait after removing the FHRP configuration? A. The VLAN interface MAC address and the FHRP MAC address are different. It takes four hours for the VLAN interface to come up.B. The SVI IP address and the FHRP IP address are different. It takes four hours for the SVI to come up.C. The VLAN interface MAC address and the FHRP MAC address are different. It takes four hours for the ARP cache to time out.D. The VLAN interface IP address and the FHRP IP address are different. It takes four hours for the VLAN interface to come up.E. The VLAN interface IP address and the FHRP IP address are different. It takes four

hours for the ARP cache to time out. Answer: C QUESTION 197 Which command is correct for creating a virtual interface on a Cisco wireless controller? A. config create interface B. tag interface C. config interface address D. untag interface Answer: C QUESTION 198 Which three series of Cisco wireless controllers support wireless Bidirectional Rate Limiting? (Choose three.) A. Cisco 2500 Series Wireless Controllers B. Cisco 5500 Series Wireless Controllers C. Cisco 5700 Series Wireless Controllers D. Cisco 7500 Series Wireless Controllers E. Cisco 8500 Series Wireless Controllers F. Cisco 7200 Series Wireless Controllers Answer: BDE QUESTION 199 Which option can use deep-packet examination to determine the specific nature of an attack? A. network IPS B. NetFlow collector C. stateful firewall D. syslog server Answer: A QUESTION 200 Refer to the exhibit. Which location is best for placing a monitor-only IPS that has visibility into the most data center traffic? A. inline before the firewall B. inline after the firewall C. passive off the firewall D. passive off the internal switch Answer: D Lead2pass.com has been the world leader in providing online training solutions for 200-310 Certification. You use our training materials that have been rigorously tested by international experts. **200-310** new questions on Google Drive: <https://drive.google.com/open?id=0B3Syig5i8gpDclAzaXozN1E0NmM> 2017 Cisco **200-310** exam dumps (All 326 Q&As) from Lead2pass: <https://www.lead2pass.com/200-310.html> [100% Exam Pass Guaranteed]